

# Optical Passives (OSP)

## OP91S2Q, OP91S4D

### Quad 1x2 and Dual 1x4 Optical Splitters/Combiners

## FEATURES

- Low insertion loss
- Operating temperature range  $-40^{\circ}$  to  $+85^{\circ}\text{C}$
- Telcordia GR-1209 and GR-1221 qualified, providing excellent environmental and mechanical stability
- MPO connectors with eight outputs
- Epoxy-free on optical path



## PRODUCT OVERVIEW

ARRIS's OP91S2Q and OP91S4D field splitters provide four separate 1x2 splitters and two 1x4 splitters, respectively, in ruggedized packages. These splitters/combiners have been designed with high uniformity and low insertion and polarization dependent loss. This product family offers balanced outputs on a standard MPO connector. Both products are designed for use in an outdoor environment within a temperature range of  $-40^{\circ}$  to  $+85^{\circ}\text{C}$ .

## SPECIFICATIONS

Characteristics	Specification																												
<b>Physical</b>																													
Dimensions	3.8" L x 3.1" W x 0.3" H (9.6 cm x 7.8 cm x 0.8 cm)																												
Weight	0.2 lb (0.9 kg)																												
<b>Environmental</b>																													
Operating Temperature Range	-40°C to +85°C (-40°F to +185°F)																												
Storage Temperature Range	-40°C to +85°C (-40°F to +185°F)																												
Humidity	5% to 95% non-condensing																												
<b>Optical</b>																													
Optical connectors	See Ordering Information																												
Splitter types (equal outputs)	<ul style="list-style-type: none"> <li>OP91S2Q: 4 independent 1x2 splitters</li> <li>OP91S4D: 2 1x4 splitters (INP A to OUTA, fibers 1-4 to MPO connector; and INP B to OUTB, fibers 5-8 to MPO connector)</li> </ul>																												
Passband wavelength	<ul style="list-style-type: none"> <li>OP91S2Q (dual windows): 1263.5 – 1357.5 nm and 1423.5 – 1617.5 nm</li> <li>OP91S4D: 1263.5 – 1617.5 nm</li> </ul>																												
Directivity, min	55 dB																												
Input power handling, max	27 dBm																												
Polarization dependent loss, max	0.15 dB																												
<b>Model-dependent parameters</b>																													
	<table border="1"> <thead> <tr> <th>Model Number</th> <th>Splitter Type</th> <th>Insertion Loss, max, with conns (dB)</th> <th>Uniformity, max (dB)</th> <th>Return Loss, min (dB)</th> <th colspan="2">Spectral Flatness (dB) over wavelength range, max</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td><b>1310 ± 20 nm</b></td> <td><b>1550 ± 20 nm</b></td> </tr> </thead> <tbody> <tr> <td>OP91S2Q-EQ-R2-MP</td> <td>Quad 1x2</td> <td>3.5</td> <td>0.4</td> <td>55</td> <td>0.15</td> <td>0.15</td> </tr> <tr> <td>OP91S4D-EQ-R2-MP</td> <td>Dual 1x4</td> <td>7.5</td> <td>0.7</td> <td>50</td> <td>0.5</td> <td>0.5</td> </tr> </tbody> </table>	Model Number	Splitter Type	Insertion Loss, max, with conns (dB)	Uniformity, max (dB)	Return Loss, min (dB)	Spectral Flatness (dB) over wavelength range, max							<b>1310 ± 20 nm</b>	<b>1550 ± 20 nm</b>	OP91S2Q-EQ-R2-MP	Quad 1x2	3.5	0.4	55	0.15	0.15	OP91S4D-EQ-R2-MP	Dual 1x4	7.5	0.7	50	0.5	0.5
Model Number	Splitter Type	Insertion Loss, max, with conns (dB)	Uniformity, max (dB)	Return Loss, min (dB)	Spectral Flatness (dB) over wavelength range, max																								
					<b>1310 ± 20 nm</b>	<b>1550 ± 20 nm</b>																							
OP91S2Q-EQ-R2-MP	Quad 1x2	3.5	0.4	55	0.15	0.15																							
OP91S4D-EQ-R2-MP	Dual 1x4	7.5	0.7	50	0.5	0.5																							

## ORDERING INFORMATION

Part Number	
OP91S2Q-EQ-R2-MP	Four 1x2 balanced splitters with 2 mm jacketed fibers in 96x78x8 mm ruggedized "F" case, with four SC/APC input connectors and one MPO/APC output connector
OP91S4D-EQ-R2-MP	Two 1x4 balanced splitters with 2 mm jacketed fibers in 96x78x8 mm ruggedized "F" case, with two SC/APC input connectors and one MPO/APC output connector

**Note:** Fiber length for all models is minimum 1 meter.

## RELATED PRODUCTS

Optical Transmitters	Optical Passives
Digital Return	Optical Patch Cords
Optical Nodes	Installation Services

## Customer Care

Contact Customer Care for product information and sales:

- United States: 866-36-ARRIS
- International: +1-678-473-5656

**Note:** Specifications are subject to change without notice.

**Copyright Statement:** ©ARRIS Enterprises, LLC, 2016. All rights reserved. No part of this publication may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS Enterprises, LLC ("ARRIS"). ARRIS reserves the right to revise this publication and to make changes in content from time to time without obligation on the part of ARRIS to provide notification of such revision or change. ARRIS and the ARRIS logo are registered trademarks of ARRIS Enterprises, LLC. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks or the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice.