

5168N

Bonded ADSL2+/VDSL2 Gateway

FEATURES

- Dual-core processor with hardware accelerated routing for exceptional performance
- ADSL/VDSL Pair Bonding
- Advanced Quality of Service for managing IPTV and any other critical data needs
- Best-in-class wireless performance, high-power wireless design
- HomePNA interface for video distribution throughout the home
- Intelligent service delivery platform
- Carrier-Quality TR-069, TR-098 and TR-104 Network Management
- Professional-Grade Firewall
- Low Total Cost of Ownership



PRODUCT OVERVIEW

The 5168N delivers best-in-class 802.11n MIMO wireless performance and HomePNA over coax for in-home network distribution of IP video.

The 5168N intelligent gateway is the optimum solution for today's service provider. It enables superior IPTV and Internet service delivery via its flexible xDSL interfaces. The 5168N terminates single-pair or pair-bonded ADSL2+/VDSL2 and automatically detects the configured profile. It can even receive a gigabit Ethernet handoff from an optical network terminal (ONT). The 5168N allows service providers to use one SKU to serve all areas of their delivery network.

ADSL/VDSL PAIR BONDING

The 5168N residential gateway features bonded ADSL2+/VDSL2 modem technology, allowing service providers to increase rate and reach with their existing broadband infrastructure.

GIGABIT SPEEDS

Enable Gigabit service offerings utilizing the integrated Gigabit Ethernet switch.

SUPERIOR WIRELESS PERFORMANCE

High-powered 802.11n 2x2 MIMO wireless technology virtually eliminates wireless “cold spots” in the home. Our intelligent gateways provide more than four times the maximum transmit power of competitive products that traditionally transmit at less than 100mW.

The 5168N gateway has superior transmit power and enhanced receiver sensitivity, in conjunction with an optimized antenna design, and boosts performance compared to typical 802.11n wireless designs. Better range throughout the home means higher customer satisfaction with wireless coverage.

STREAMLINED MANAGEMENT

The 5168N intelligent gateway drastically simplifies both gateway and application management; remote management is supported with any TR-069-compliant auto-configuration server, such as our industry-leading ECO Manage device management system.

ECO Manage gives providers a valuable insight into the customer’s network, enabling them to remotely configure, manage and troubleshoot deployed gateway devices, eliminating costly truck rolls and lengthy customer care calls. Additionally, IP-based services can be remotely managed using the web-based ECO Service Management tools. ECO Service Management can reduce operational expenses, shorten time-to-market for next-generation services, and increase customer satisfaction.

MAIN INTERFACES

- Bonded ADSL2+/VDSL2
- Gigabit Ethernet WAN
- HomePNA 3.1 coax port
- 4 x Gigabit Ethernet LAN ports
- 802.11n 2x2 MIMO Wi-Fi
- USB Host Port

GENERAL SPECIFICATIONS

Broadband Network Interfaces

Integrated Bonded ADSL2+/VDSL2 Modems (1 RJ-14)

Gigabit Ethernet (1 RJ-45)

Broadband interface auto detection feature

DSL Modem

ADSL 1, ADSL 2, ADSL 2+

VDSL2

T1.413 Issue 2, G.992.1, G.992.3, G.992.5, G.HS/G.994.1

VDSL-DMT per G.993.2 standard

Ethernet Bonding G.998.2

TR-067- and TR-100-compliant

ANSI and ETSI loops

Annex A, L and M support

Extended frames support

Cabinet mode support

High-Powered Wireless Functionality

IEEE 802.11n 2x2 2.4 GHz wireless access point, backwards compatible with 802.11b/g

10 power settings available through gateway user interface, up to 25 +/- 1dBm, for 802.11b, 802.11g, and 802.11n

Settings also configurable via CWMP

WEP64, WEP128, WPA, WPA2

Automatic channel selection with interference detection

Multiple SSID support

Wi-Fi Multimedia (WMM) and Multimedia Power Save (WMM-PS)

MAC-based filtering

Wi-Fi Protected Setup (WPS)

Local Network Interfaces

Gigabit (10/100/1000 Mbps) Ethernet (4 ports RJ-45)

Wireless 802.11b/g/n access point

HomePNA 3.1 interface over coax

1 x USB 2.0 Host interface (2 option)

GENERAL SPECIFICATIONS

Software Tools and Diagnostics

Zero-touch subscriber activation including Captive Portal

Simple Web-based user interface for easy configuration and diagnostics

Quick summary page with shortcuts to most commonly used features

Standard and advanced DSL Diagnostics provided as TR-098 vendor extensions

Network Protocol Support

ATM UNI, UBR, VBRnrt, VBRrt, CBR

IPv4, IPv6 6RD, TCP, UDP, ARP, ICMP

DHCP client/server, DNS client/server, HTTP client/server

Single IP and multi-IP support

PPPoE, PPPoA, PAP, CHAP, RFC 2684/1483 Ethernet

IGMP Proxy and Snooping

QOS

Diffserv

802.1p/q

Traffic shaping and policing

Traffic remarking and passthrough

Device generated traffic marking

DHCP, NTP, TR-69, DNS

Diagnostics and Management Tools

Remote management and provisioning via SSL connection from ECO Manage or other TR-069-compliant ACS

Supports TR-069, TR-098, and TR-104

Integrated gateway-based diagnostics automatically intervene during error conditions, such as Missing Filter Detection, intercept subscriber Web requests, and provide self-guided resolutions

Web-based remote gateway technician view and remote management

ICMP Ping, Traceroute

Multicolor indicator lights monitor the connection and assist with troubleshooting

GENERAL SPECIFICATIONS

Security

Integrated firewall includes stateful packet inspection (Layer 4) and local IP spoofing verification

Supports stealth mode operation

Unique signed security certificate manufactured into each gateway for TR-069 management authentication

NAT/PAT Support

Standard NAT/PAT between LAN and WAN

Automated NAT pass-through for LAN client-initiated VPN tunnels (IPSec, PPTP, L2TP), SIP, H.323, RTP

Easy-to-configure NAT pass-through (pinholes) for common applications (games, servers, etc.)

DMZplus for automatic WAN IP assignment to a local computer

Supports most popular ALGs: HTTP, FTP, H.323, IPSEC-IKE/ESP, PPTP, RTP, RTSP, and SIP

Software Upgrade

Secure TR-069 software updates procedure via ECO Manage

Standard Hardware Features

TR-068-compliant industrial design and LED indicators

Vertical placement via provided stand or horizontal desktop placement

Wall mount capable (with optional bracket)

GENERAL SPECIFICATIONS

Physical Specifications

With stand: 3.1" x 9.6" x 9.7" (7.8 cm x 24.3 cm x 24.5 cm)

Without stand: 1.6" x 8.7" x 8.9" (4.0 cm x 22.1 cm x 24.6 cm)

1.6 lbs (0.70 kg)

Power Supply

External PSU: 12V, 3A

2-prong ungrounded non-polarized AC plug

Memory

Up to 128 MB Flash (64 MB standard)

Up to 256 MB RAM (128 MB standard)

Operating Environment

Temperature: 32° to 104° F (0° to 40° C)

Humidity: 5% to 95%, non-condensing

Altitude: -197' – 6,000' MSL

CUSTOMER CARE

Contact Customer Care for product information and sales:

- United States: 866-36-ARRIS
- International: +1-678-473-5656