

SFP Fiber Optic Transceivers

TFB1550-TF17

125 Mbps Bi-Directional Optical Transceiver Module
(1550 nm Tx/1310 nm Tx)

FEATURES

- 125 Mbps data throughput
- Pluggable SFP MSA 8472 Rev 9.3 compliant
- Simplex LC/UPC connector
- Tx/Rx distance up to 20 km over SMF
- 1550 nm laser diode transmitter
- Extended operating temperature range (-40°C to +85°C)



PRODUCT OVERVIEW

The TFB1550-TF17 Bi-Directional Optical Transceiver Module is ideally suited for Fast Ethernet and PON applications where a single fiber is required to simultaneously carry both Tx and Rx signals up to 20 km (over SMF). The built-in high isolation WDM enables full duplex operation.

Conforming to the Small Form Pluggable (SFP) Multisource Agreement for a 2x10 package with a Simplex LC/UPC optical connector, these state-of-the-art components are designed expressly for bi-directional communication applications that require rates of up to 125 Mbps. The transmitter and receiver subassemblies incorporate a high performance 1550 nm FP laser assembly and high sensitivity 1310 nm PIN/TIA photo receiver.

The TFB1550-TF17 features a very low jitter contribution, resulting in extremely clean, high-quality eye patterns. The module operates over extended temperature (-40° to $+85^{\circ}\text{C}$) ranges, and dissipates less than 700 mW. The Class I laser transmitter complies with applicable safety standards (IEC 60825-1, FDA 21, CFR 1040.10 and 1040.11).

SPECIFICATIONS

Characteristics	Specification
Physical	
Dimensions	2.2" L x 0.4" H x 0.5" W (5.6 cm x 1.0 cm x 1.3 cm)
Weight	0.1 lbs (0.05 kg)
Environmental	
Application temperature range	-40° to $+85^{\circ}\text{C}$ (-40° to $+185^{\circ}\text{F}$)
Storage temperature range	-40° to $+85^{\circ}\text{C}$ (-40° to $+185^{\circ}\text{F}$)
Humidity	5% to 95% non-condensing
Optical Interface	
Optical connectors	Simplex LC/UPC
Power requirements	
Input voltage	3.3 V_{DC} (160 mA)
Power consumption	1 W max
General	
Hot plug-in/out	
Regulatory	
Laser Class 1 devices per FDA/CDRH and IEC 60825-1	
Optical	
Transmitter:	
Wavelength	1510–1580 nm (1550 nm typical)
Signaling speed	125 Mbps
Optical output power with 9/125 μ SMF	-14 dBm min
Extinction ratio (ER)	8 dB min
Receiver:	
Receiver type	PIN/TIA
Wavelength	1260–1310 nm
Received optical power with 9/125 μ SMF	-31 to -3 dBm
System:	
WDM crosstalk (optical), max	-40 dB
Power budget, min with 9/125 μ SMF	17 dB
Fiber span, max with 9/125 μ SMF	20 km

RELATED PRODUCTS

Fast Ethernet applications

ORDERING INFORMATION

T	F	B	1	5	5	0	-	T	F	1	7

125 Mbps Bi-directional SFP Optical Transceiver Module
(1550 nm Tx/1310 nm Rx)

Customer Care

Contact Customer Care for product information and sales:

- United States: 866-36-ARRIS
- International: +1-678-473-5656

Note: Specifications are subject to change without notice.

Copyright Statement: ©ARRIS Enterprises, LLC, 2016. All rights reserved. No part of this publication may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS Enterprises, LLC ("ARRIS"). ARRIS reserves the right to revise this publication and to make changes in content from time to time without obligation on the part of ARRIS to provide notification of such revision or change. ARRIS and the ARRIS logo are registered trademarks of ARRIS Enterprises, LLC. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks or the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice.