


# Optical Node Series

VTN-ITU-CH-\*

DWDM Analog Return Transmitters

## FEATURES

- Enables bandwidth expansion via upstream node segmentation
- DWDM models accommodate a wide variety of network architectures
- Supports migration to fiber deep networks by maximizing fiber usage
- Hot swappable, plug and play modules simplify installation and maintenance
- 5 to 204 MHz RF Passband to support DOCSIS 3.1



## PRODUCT OVERVIEW

ARRIS increases the segmentation options for the VTN244 1 GHz optical node with the introduction of analog Dense Wave Division Multiplex (DWDM) return path transmitters. These transmitters provide an ideal solution when network designs call for more wavelength aggregation or greater link distance than CWDM transmitters can provide.

The VTN-ITU-CH\* transmitters feature cooled, 8 dBm Distributed Feedback (DFBT) lasers based on the International Telecommunications Union (ITU) wavelength grid. Without amplification, the typical link budget is 14 dB. When needed, the VTN-ITU-CH\* DWDM signals can be amplified by Erbium Doped Fiber Amplifiers (EDFA) to overcome large link budgets similar to digital return links.

The VTN-ITU-CH\* is supported by the VTN-DOCSIS status monitor transponder. Parameters for control and monitoring include optical output power, laser bias current, and supply current.

## SPECIFICATIONS

Available Wavelength Range	ITU CH 20 – 60
Wavelength Stability	± 0.08 nm Max.
Optical Output Power	8.0 ± 0.4 dBm
Optical Power Test Point	1.0 ± 0.15 mW/V
Optical Modulation Index	20.0 ± 2.0 %
RF Bandwidth	5 MHz to 204 MHz
Frequency Response Flatness	± 0.5 dB Max.
RF Return Loss	16 dB Min.
Nominal RF Input Level (Total Power) <sup>1</sup>	18 dBmV
Dynamic Range For NPR >= 40 dB <sup>2</sup>	15 dB
Supply Current +5.75 V Supply	600 mA Max.
Dimensions	4.0 in L x 0.86 in W x 2.4 in D (104 x 22 x 62 mm)
Weight	1 lb (0.45 kgs)
Operating Temperature Range (Node)	–40° F to 140° F (–40° C to 60° C)

### Notes:

1. Recommended Total RF Power at the Node Housing Port is 28 dBmV.
2. 37 MHz Loading (5 MHz – 42 MHz) 40 km SMF 28 fiber, plus passive loss to obtain –6 dBm optical input to receiver

## RELATED PRODUCTS

DOCSIS Transponder	Ingress Control Switches
Power Supplies	Optical Passives
Fiber Service Cable	Installation Services

## Customer Care

Contact Customer Care for product information and sales:

- United States: 866-36-ARRIS
- International: +1-678-473-5656

**Note:** Specifications are subject to change without notice.

**Copyright Statement:** ©ARRIS Enterprises, Inc. 2015 All rights reserved. No part of this publication may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS Enterprises, Inc. ("ARRIS"). ARRIS reserves the right to revise this publication and to make changes in content from time to time without obligation on the part of ARRIS to provide notification of such revision or change. ARRIS and the ARRIS logo are all registered trademarks of ARRIS Enterprises, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice.

VTN-ITU-CH\_DS\_27APR15

(rev 04-2015)

Ask us about the complete Access Technologies Solutions portfolio:

Nodes-VTN-ITU